

Application No: 10/665,687 Docket No.: Q137-US6

Page 6

REMARKS

Claims 1-42 and 46-66 are canceled. Claims 43-45, and 67-90 were previously presented. Accordingly, claims 43-45, and 67-90 are pending examination.

Traversal of Restriction Requirement

The pending Office Action includes a Restriction Requirement with respect to claim 90.

Upon receipt of the Advisory Action, the Applicant will be re-entering this Application into the Appeals process. However, the Applicant will also be submitting a Petition to Withdraw this Restriction Requirement Under 37 C.F.R. §1.144. In order to submit this, the Applicant needs the Restriction Requirement to be made final. As a result, the following is a traversal of the Restriction Requirement.

The Restriction Requirement is based on an argument that 90 is directed to a method of disassembling a battery. Claim 90 recites a battery. For instance, claim 90 recites "the battery of claim 68." Further, the limitations recited in claim 90 are structural limitations. For instance, the claim 90 includes the following language: "the tab is connected to the second end cap such that..." This language limits the structural relationship between the tab and the cap. Accordingly, claim 90 is directed to a battery and properly narrows the battery of claim 43.

Since claim 43 is not directed to a method, the Applicant requests rejoinder of claim 90.

Rejection of Claim 89 Under 35 USC §112

Figure 21 illustrates a battery where "the tab is the only tab providing electrical communication between the second end cap and the electrode that is electrically insulated from the pin" as recited in claim 89.

Application No: 10/665,687 Docket No.: Q137-US6

Page 7

Rejection of Claim 43 Under 35 USC §103

The arguments submitted in Applicant's the prior response are re-asserted below and will be presented during appeal.

Claims 43 stands rejected under 35 USC §103(a) as being unpatentable over U.S. Patent No. 6,399,242 (Kitoh) and U.S. Patent No. 3,159,508 (Chreitzberg).

1. MPEP 2144.04(VI)(C) does not apply

The pending rejection relies at least partly on the case of *In re. Japiske*, 181 F.2d 1019, 86 USPQ 70 (CCPA 1950). This case is cited in MPEP 2144.04(VI)(C). The heading of MPEP 2144.04(VI)(C) is "*Rearrangement of Parts.*" Accordingly, this portion of the MPEP is directed to the law for rejections based on an argument that an Applicant has merely re-arranged parts of a prior art device.

The entire text of MPEP 2144.04(VI)(C) appears as follows:

C. Rearrangement of Parts

In re Japiske, 181 F.2d 1019, 86 USPQ 70 (CCPA 1950) (Claims to a hydraulic power press which read on the prior art except with regard to the position of the starting switch were held unpatentable because shifting the position of the starting switch would not have modified the operation of the device.); *In re Kuhle*, 526 F.2d 553, 188 USPQ 7 (CCPA 1975) (the particular placement of a contact in a conductivity measuring device was held to be an obvious matter of design choice). However, "The mere fact that a worker in the art could rearrange the parts of the reference device to meet the terms of the claims on appeal is not by itself sufficient to support a finding of obviousness. The prior art must provide a motivation or reason for the worker in the art, without the benefit of appellant's specification, to make the necessary changes in the reference device." *Ex parte Chicago Rawhide Mfg. Co.*, 223 USPQ 351, 353 (Bd. Pat. App. & Inter. 1984). (Underlining and bolded sections added by Applicant)

As is evident from the bolded portion of the text this section of the MPEP(VI)(C) applies when the "rearrangement or parts" is a matter of design choice.

Application No: 10/665,687 Docket No.: Q137-US6

Page 8

The location of the tab recited in the claim 43 is not a mere matter of design choice. For instance, as stated in the specification, the claimed tab location can **“obviate... the need for a separate electrolyte fill port, thereby reducing the number of components and number of seals to be made, thus reducing cost and improving reliability.”** The specification describes this as follows:

In accordance with a preferred embodiment, the tab 94 is sufficiently long to locate the weld 110 beyond the center point of the circular endcap 114. More particularly, note in FIGS. 21-24 that by locating the weld 110 displaced from the center of the cap 114, the tab 94 can conveniently support the endcap 114 in a vertical orientation as depicted in FIG. 22 misaligned with respect to the open end 106. This end cap position approximately perpendicular to the end 122 of the case 100 is a first bias position wherein the end cap advantageously tends to remain in that orientation with the case end open prior to filling. To further describe the relationship between the weld location and the various components, FIG. 23 shows a front view with various dimensions. L represents the length from the weld 110 to the top of the case 100 as measured parallel to the edge of the case. R is the radius of the end cap 114. For the preferred geometry, $L \leq 2R$. Weld 110 is preferably made above the center point 111 of the end cap 114. Preferably, the end cap 114 overlaps the case 100 by approximately $R/2$. By configuring the tab 94 and weld 110 as indicated, the endcap 114 can be supported so that it does not obstruct the open end 106, thereby facilitating electrolyte filling of the case interior cavity via open end 106. A filling needle or nozzle can be placed through open end 106 to fill the case. **This obviates the need for a separate electrolyte fill port, thereby reducing the number of components and number of seals to be made, thus reducing cost and improving reliability.**

Furthermore, for small medical batteries, the end caps would be very small to have fill ports therein. In a preferred embodiment in which the case wall is very thin, for example, 0.002 inches, providing a fill port in the side wall of the case would be impractical. Even in the case of larger devices

Application No: 10/665,687 Docket No.: Q137-US6

Page 9

where space is less critical and the wall is more substantial, providing a fill port in the side of the case would mean the electrolyte would have a very long path length to wet the jellyroll. Note that while the case could be filled with electrolyte prior to welding tab 94 to endcap 114, it would be difficult and messy to do so. Therefore, it is advantageous to configure the tab 94 and weld 110 as described to allow the weld to be made prior to filling.

Since the claimed tab location can “obviate... the need for a separate electrolyte fill port, thereby reducing the number of components and number of seals to be made, thus reducing cost and improving reliability,” there is no reasonable argument that this is a mere design choice. Since the claimed tab location is not a mere matter of design choice shows that MPEP(VI)(C) is not properly applied to this rejection.

Additionally, the portion of MPEP(VI)(C) that that Applicant underlined above states that “(t)he prior art must provide a motivation or reason for the worker in the art, without the benefit of appellant's specification, to make the necessary changes in the reference device.” The motivation set forth in the Office Action is that the proposed modification would “reduce internal resistance and facilitate current extraction.” Nothing in any of the cited art indicates that making the suggest modification would reduce internal resistance or improve “current extraction.” Since the motivations for the proposed modification cannot be found in the cited art as is required for the proper application of MPEP(VI)(C), this section of the MPEP is not properly applied to this rejection.

2. There Is No Motivation to Make the Proposed Modification

The Office Action proposes attaching Kitch's tabs as taught by Chreitzberg's. The Office Action states that the motivation for the proposed modification is to “reduce internal resistance and facilitate current extraction.”

The Office Action analogizes Chreitzberg's conductors 8, 11 to the claimed tab. However, the ONLY teachings that Chreitzberg provides about these conductors 8, 11 are shown in Figure 1 and in the following text:

Application No: 10/665,687 Docket No.: Q137-US6

Page 10

Each of the negative electrodes 3 is connected to the negative terminal of the battery 7 by means of a conductor 8. Similarly, each of the positive electrodes 4 is connected to the positive terminal of the battery 9 by means of a conductor 11. There is nothing about these teachings that even suggests that the arrangement of the Chreitzberg's conductors 8, 11 would "reduce internal resistance and facilitate current extraction" in Itoh's battery. As a result, the motivation for the proposed modification cannot be found in the cited art.

The KSR decision finds that the motivation for a proposed modification can also come from common sense. However, common sense indicates that the stated motivation is not accurate. For instance, since Itoh's tabs are shown positioned in one half of the battery, modifying Itoh as proposed would lengthen Itoh's tabs. Increasing the length of a tab increases the resistance provided by that tab and accordingly increases the internal resistance of the battery. Further, increasing the internal resistance of the battery cannot be considered to facilitate current extraction. As a result, common sense does not lead one to conclude that re-locating Itoh's tabs as suggested would "reduce internal resistance and facilitate current extraction."

Due to the lack of reasoning for the stated motivation in either the cited art or in common sense, the only motivation for the proposed modification appears to be found in the Applicant's specification. As a result, it logically follows that the basis for the proposed modification has been improperly gleaned from Applicant's own specification and that the combination of the cited is an exercise of impermissible hindsight. Accordingly, it is respectfully submitted that the combination is improper and respectfully requested that the rejection be withdrawn.

3. The Cited Art Does Not Teach or Suggest Every Limitation of the Claims

Itoh teaches a battery having a single terminal 15 centered in each one of its endcaps. In order for Itoh to be modified so it includes all of the limitations of claim 43, one of Itoh's terminals must be moved from its current location to a location that is off center in the cap. Chreitzberg teaches multiple terminals extending through a single top seal 2. Since multiple terminals extend through a single "top seal 2," at least one of the terminals must be off center relative in the "top seal." There is nothing about multiple

Application No: 10/665,687 Docket No.: Q137-US6

Page 11

terminals extending through a single cap that suggests that Kitoh's centered terminal be moved to an off-center location. This is even more true when it is realized the Kitoh's terminal is centered relative to Kitoh's tabs and moving the terminal would disrupt this arrangement. As a result, the cited art does not teach or suggest all of the limitations of claim 43.

Rejection of claims 44-45, and 67-90

Claims 44-45, and 67-90 each depends directly or indirectly from independent claim 43. Since claim 43 is believed to be in condition for allowance, these claims are also believed to be in condition for allowance.

Application No: 10/665,687

Docket No.: Q137-US6


Page 12
RECEIVED
CENTRAL FAX CENTER

JUL 21 2010

CONCLUSION

Applicant submits that the claims define patentably over the prior art and that this application is in condition for allowance. Accordingly, favorable consideration and allowance of this application is courteously requested.

The Examiner is encouraged to telephone the undersigned with any questions.



Travis Dodd
Reg. No. 42,491
Agent for Applicant(s)

Quallion LLC
P.O. Box 923127
Sylmar, CA 91392-3127
818-833-2003 ph
818-833-2065 fax
travisd@quallion.com